

## **Specification Sheet**

# Élan-08R-360 Underfloor Air Diffuser Terminal (Constant Volume)


### Description

**Élan-08R-360 (Personal Comfort Diffuser)** is an adjustable constant volume air terminal for use in raised floor air systems. It features an 18 gauge (1.3mm) galvanized steel catch pan assembly, with all interior features pre-painted flat black.


The nominal 8" (203mm) diameter cast aluminum grille produces 360 degree omni-directional mixing air flow. A manually adjustable sliding damper allows space occupants to limit maximum air flow. Ten (10) standard grille colors are available; custom colors and finishes can be provided to match architectural design (specify on order).

#### **Features**

- · Ships fully assembled; installation in seconds
- · Manual air flow adjustment with sliding damper
- Durability (as strong as the floor)
- · Non-binding flow adjustment
- · No "clear area" required
- · Tight shut-off







ALL DIMENSIONS NOMINAL +/- 0.1" (2.5mm)

#### **Specifications**

Application:Underfloor Cooling | Raised Access Floors 8" (203mm) +Grille Dimensions:Diffuser Opening: 8"Ø (203mm) | Full Face: 9.5"Ø (241mm)Diameter (Nominal)Installation Cut-Out: 8.3125"Ø [+.125/-.00] (211mm [+3.175/-.00])

Grille Rating: Cast Aluminum | Conforms to NFPA 90a | 1250 lbs. (567 Kg) Load Strength

**Supply Press. / Temp.:** 0.02–0.1 in. w.c. (5–25 Pa) | 40–140°F (4–60°C)

Capacity: Maximum: 81 cfm @ 0.05 in. w.c. (138 m³/hr @ 12.5 Pa)

(Nominal) Minimum (Damper Closed): 7 cfm @ 0.05 in. w.c. (12 m³/hr @ 12.5 Pa)

Noise Criterion: ≤ NC-17 (All Flow Conditions)